

SOLEN INC.

4470 Ave. Thibault
 St-Hubert, QC J3Y 7T9 CANADA
 Tel: 450-656-2759 Fax: 450-443-4949

Aurasound

Neo Radial Technology
 Made in U.S.A.
 solen@solen.ca

| P/N | Size | VC | Type | | dB | W | Z | Re | Le | Ce | Fs | Vas | Qms | Qes | Qts | Xmax | Cutout |
|-------------------|--|------|---------|------|------|------|----------|----------|-----|---------|-----|-----|-----|-----|-----|------|--------|
| AUDIO HIFI | mm | mm | | | 2.8V | | Ω | Ω | mH | μ F | Hz | li | | | | mm | mm |
| EXT. RANGE | | | | | | | | | | | | | | | | | |
| NSW1-205-8A | 38mm | 20mm | Tita | Cone | 78 | 20 | 8 | 6.3 | .10 | 2.7 | 220 | .04 | 2.1 | 1.1 | .70 | ±3.0 | *35 |
| NSW2-326-8A | 49mm | 32mm | Tita | Cone | 84 | 60 | 8 | 6.4 | .23 | 5.6 | 250 | .10 | 4.7 | .80 | .68 | ±5.0 | *47 |
| WOOFER | | | | | | | | | | | | | | | | | |
| NS3-193-4A | 89mm | 19mm | AL | Cone | 81 | 80 | 4 | 3.5 | .33 | 27 | 78 | 1.3 | 9.0 | .62 | .58 | ±10 | *78 |
| NS3-193-4A1 | 89mm | 19mm | AL | Cone | 81 | 80 | 4 | 3.5 | .33 | 27 | 78 | 1.3 | 9.0 | .62 | .58 | ±10 | *78 |
| NS3-193-8A | 89mm | 19mm | AL | Cone | 81 | 80 | 8 | 7.6 | .37 | 6.8 | 70 | 1.3 | 8.0 | .73 | .67 | ±10 | *78 |
| NS3-193-8A1 | 89mm | 19mm | AL | Cone | 81 | 80 | 8 | 7.6 | .37 | 6.8 | 70 | 1.3 | 8.0 | .73 | .67 | ±10 | *78 |
| NS4-255-4D | 11cm | 25mm | AL | Cone | 84 | 80 | 4 | 3.6 | .56 | 43 | 57 | 3.8 | 7.0 | .41 | .39 | ±10 | *100 |
| NS4-255-4D1 | 11cm | 25mm | AL | Cone | 84 | 80 | 4 | 3.6 | .56 | 43 | 57 | 3.8 | 7.0 | .41 | .39 | ±10 | *100 |
| NS4-255-8D | 11cm | 25mm | AL | Cone | 84 | 80 | 8 | 6.2 | .86 | 22 | 62 | 3.2 | 7.4 | .47 | .44 | ±10 | *100 |
| NS4-255-8D1 | 11cm | 25mm | AL | Cone | 84 | 80 | 8 | 6.2 | .86 | 22 | 62 | 3.2 | 7.4 | .47 | .44 | ±10 | *100 |
| NS10-513-4A | 27cm | 51mm | AL | Cone | 84 | 200 | 4 | 3.0 | | | 29 | 54 | 9.4 | .35 | .34 | ±10 | 226 |
| NS12-513-4A | 32cm | 51mm | AL | Cone | 85 | 200 | 4 | 2.9 | | | 23 | 127 | 9.1 | .39 | .37 | ±10 | 280 |
| SUBWOOFER | | | | | | | | | | | | | | | | | |
| NS10-794-4A | 27cm | 79mm | AL | Cone | 85 | 1000 | 4 | 3.6 | .55 | 47 | 32 | 33 | 7.8 | .42 | .40 | ±18 | 233 |
| NS12-794-4A | 32cm | 79mm | AL | Cone | 86 | 1200 | 4 | 3.5 | .55 | 47 | 27 | 78 | 7.1 | .45 | .43 | ±18 | 280 |
| NS15-992-4A | 39cm | 10cm | AL | Cone | 86 | 1500 | 4 | 3.3 | | | 20 | 169 | 8.0 | .40 | .37 | ±25 | 352 |
| NS18-992-4A | 48cm | 10cm | AL | Cone | 87 | 1800 | 4 | 3.1 | | | 20 | 322 | 7.7 | .50 | .47 | ±25 | 427 |
| BASSSHAKER | | | | | | | | | | | | | | | | | |
| AST-2B-4 | 16cm | 50mm | Exciter | | | 50 | 4 | | | | | | | | | | |
| AST-3B-4 | 2x AST-2B-4 with 100w 12v Car Amplifier | | | | | | | | | | | | | | | | |
| AMP-50 | 60W 120v Amplifier | | | | | | | | | | | | | | | | |
| AMP-RC24 | 2.4GHz Receiver for AMP-50 | | | | | | | | | | | | | | | | |
| AMP-TR24-T | 2.4GHz Transmitter for AMP-50 | | | | | | | | | | | | | | | | |
| AMP-TR24-PS | Power Supply for AMP-TR24-T | | | | | | | | | | | | | | | | |
| DSK-50 | Drum Throne Bass Shaker (AST-2B-4 + Bracket) | | | | | | | | | | | | | | | | |

Specifications are subject to change without notice.